



Wall mounted Alpha

FAA-A / RZAG-N *SkyAir Alpha-series*

R-32 BLUEEVOLUTION

Conveniently surface mounted
Also for rooms with no false ceilings

- › Combinations with Sky Air Alpha series ensures best in class quality, highest efficiency and performance
- › Flat, stylish front panel blends easily within any interior and is easier to clean
- › Can easily be installed in both new and refurbishment projects
- › Reduced energy consumption thanks to specially developed DC fan motor
- › The air is comfortably directed up and down to suit your needs, thanks to 5 different discharge angles that can be programmed via the remote control
- › Maintenance operations can be performed easily from the front of the unit



FAA-A



RZAG71-100



BRC1H519W7



BRC7EB518 (optional)



BRP069A81 (optional)



WI-FI ADAPTOR
AVAILABLE AS AN OPTION

FAA-A / RZAG-N

R-32 BLUEEVOLUTION

Indoor Units			Single Phase		3 Phase	
			FAA71A	FAA100A	FAA71A	FAA100A
Capacity	UK Total Cooling	kW	7.76	10.85	7.76	10.85
	UK Sensible Cooling	kW	5.32	7.44	5.32	7.44
	Nominal Cooling	kW	6.8	9.5	6.8	9.5
	Nominal Heating	kW	7.5	10.8	7.5	10.8
Seasonal Efficiency (EN14825) COOLING	Energy Label		A++	A++	A++	A++
	Pdesign	kW	6.8	9.5	6.8	9.5
	SEER		6.58	6.42	6.58	6.42
	Annual Energy Consumption	kWh	362	518	362	518
Seasonal Efficiency (EN14825) HEATING	Energy Label		A+	A+	A+	A+
	Pdesign	kW	4.7	7.8	4.7	7.8
	SCOP		4.2	4.01	4.2	4.01
	Annual Energy Consumption	kWh	1567	2723	1567	2723
Nominal Efficiency	EER/COP		3.27/5.14	3.74/5.19	3.27/5.14	3.74/5.19
Air Flow Rate (Cooling)	High / Nom / Low	m ³ /sec	0.300/0.266/0.233	0.433/0.383/0.316	0.300/0.266/0.233	0.433/0.383/0.316
Dimensions	Height	mm	290	340	290	340
	Width	mm	1050	1200	1050	1200
	Depth	mm	238	240	238	240
Weight		kg	13	17	13	17
Sound Pressure (Cooling)	High / Nom / Low	dBA	45/42/40	49/45/41	45/42/40	49/45/41
Sound Pressure (Heating)	High / Nom / Low	dBA	45/42/40	49/45/41	45/42/40	49/45/41
Sound Power (Cooling)		dBA	61	65	61	65

Outdoor Units			RZAG71NV1	RZAG100NV1	RZAG71NY1	RZAG100NY1
Dimensions	Height x Width x Depth	mm	870 x 1100 x 460	870 x 1100 x 460	870 x 1100 x 460	870 x 1100 x 460
Weight		kg	81	85	81	85
Electrical Details	Power Supply		1ph	1ph	3ph	3ph
	Maximum Input Current (MCA) A		17.5	21.3	10.9	14.0
	Max Fuse Size	A	20	32	16	16
Interconnection Wiring	Core / Cable Size		3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)
Pipework	Maximum Length	m	55	85	55	85
	Maximum Vertical Rise	m	30	30	30	30
	Precharged to	m	40	40	40	40
	Additional charge	g/m	Refer to Installation Manual		Refer to Installation Manual	
	Holding charge	kg	3.2	3.2	3.2	3.2
Sound Pressure (Cooling)	Nom / Night Quiet	dBA	46/44	47/45	46/44	47/45
Sound Pressure (Heating)	Nom / Night Quiet	dBA	48/44	50/45	48/44	50/45
Sound Power (Cooling)		dBA	64	66	64	66
Operating Range (Cooling)	Min / Max	°CDB	-20/52	-20/52	-20/52	-20/52
Operating Range (Heating)	Min / Max	°CWB	-20/18	-20/18	-20/18	-20/18
Air Flow Rate (Cooling)	Nominal	m ³ /sec	1.133	1.117	1.133	1.117

Accessory Ref	Description
BRP069A81	Wifi adaptor for connection to on-line controller
BRC1H519W7	Wired touch screen remote controller - White (Included as standard)
BRC1H519S7	Wired touch screen remote controller - Silver
BRC1H519K7	Wired touch screen remote controller - Black
BRC7EB518	Wireless remote controller
K.CGM	Condensing unit guard size Split 42-71/ Sky Air 35-250
K.CWBXL	Wall Brackets SS (250kg, 600mm)
K.DT2	Condensate drip tray for use with K.CWBXL
SB.K.RSS_RFC	Wireless room mounted temperature sensor and receiver
KLIC-DI	KNX Interface for Sky Air and VRV systems
KRCS01-4	Remote room mounted temperature sensor
KRP4A53 and UK.FB2	Unit/group adaptor PCB for remote on/off, status indication and temperature setting
RS-SE	Service and configuration tool for K.RSS
RTD-10 and UK.FB2	Enhanced function PCB for Sky Air and VRV. Duty rotation, Lead Lag control and heating interlock
RTD-20 and UK.FB2	Energy control PCB for Sky Air and VRV
RTD-NET and UK.FB2	Modbus interface PCB for Sky Air and VRV

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com