



Flexi- floor or ceiling mounted

Compact unit for flexible install location

FLXS-B(9) / RXS-L

Flexible unit, ideal for rooms without false ceiling

Can fit on either ceiling or lower wall; its low height enables the unit to fit beneath a window:

- > Home leave operation maintains the indoor temperature at your specified comfort level during absence, thus saving energy
- > Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- > Online controller: controls your indoor from any location with an app, via your local network or internet



ARC433A6



RX(K)S20-25-35



FLXS50

Features	Benefits
Low height	Enables the unit to fit beneath a window
Flexibility in whether can fix horizontally or vertically	Can fit on either ceiling or lower wall
Home leave operation maintains the indoor temperature at your specified comfort level during absence	Saves energy and maintains comfort levels
Night set mode preventing overcooling or overheating during night time	Reduces energy consumption
Vertical auto swing moves the discharge louvres up and down	Maintains efficient air and temperature distribution throughout the room
Online controller	Control your indoor from any location with an app, via your local network or internet

FLXS-B(9) / RXS-L

Indoor Units			FLXS25B	FLXS35B9	FLXS50B
Capacity	UK Total Cooling	kW	2.44	3.34	4.82
	UK Sensible Cooling	kW	1.65	2.14	3.16
	Nominal Cooling	kW	2.50	3.50	4.90
	Nominal Heating	kW	3.40	4.00	6.10
Seasonal Efficiency (EN14825) COOLING	Energy Label		A	B	A
	Pdesign	kW	2.50	3.50	4.90
	SEER		5.19	4.87	5.25
	Annual Energy Consumption	kWh	169	252	326
Seasonal Efficiency (EN14825) HEATING	Energy Label		A	A	A
	Pdesign	kW	2.50	2.90	4.20
	SCOP		3.80	3.80	3.80
	Annual Energy Consumption	kWh	921	1068	1546
Nominal Efficiency	EER / COP		3.85 / 3.54	2.88 / 3.57	2.85 / 3.35
	Energy Label		A / B	B / B	C / C
	Annual Energy Consumption	kWh	325	608	860
Air Flow Rate (Cooling)	High / Nom / Low / Silent	m ³ /sec	0.127 / 0.127 / 0.100 / 0.087	0.143 / 0.127 / 0.110 / 0.093	0.190 / 0.190 / 0.142 / 0.125
Dimensions	Height	mm	490	490	490
	Width	mm	1050	1050	1050
	Depth	mm	200	200	200
Weight		kg	16	16	17
Sound Pressure (Cooling)	High / Nom / Low / Silent	dBA	37 / 34 / 31 / 28	38 / 35 / 32 / 29	47 / 43 / 39 / 36
Sound Power		dBA	51	53	60

Outdoor Units			RXS25L3	RXS35L3	RXS50L
Dimensions	Height x Width x Depth	mm	550 x 765 x 285	550 x 765 x 285	735 x 825 x 300
Weight		kg	34	34	47
Electrical Details	Power Supply			1ph	
	Running Current	A	3.60	5.10	7.60
	Starting Current	A	3.3	4.3	6.8
	Max Fuse Size	A	10	10	20
Interconnection Wiring	Core / Cable size		3+E / 1.5		3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	1/4 (6.4) / 3/8 (9.5)		1/4 (6.4) / 1/2 (12.7)
Pipework	Maximum Length	m	20	20	30
	Maximum Vertical Rise	m	15	15	20
	Precharged to	m	10	10	10
	Additional Charge	g/m		20	
	Holding Charge	kg	1.0	1.2	1.7
Sound Pressure (Cooling)	High / Silent Operation	dBA	46 / 43	48 / 44	48 / 44
Sound Power		dBA	59	61	62
Air Flow Rate (Cooling)	High	m ³ /sec	0.558	0.600	0.848

Accessories	Material	
Wired remote control	BRC073A1	Hard wired remote controller – identical appearance to standard Daikin BRC1E53 VRV / SkyAir remote controller
Wired remote control	BRC944B2	Hard wired remote controller – similar appearance to older Daikin BRC1D52 VRV / SkyAir remote controller
Extension cord for wired remote control [3m]	BRCW901A03	3 metre cord to connect hard wired remote controller to fan coil unit – a connection cord (3 or 8m cord is required)
Extension cord for wired remote control [8m]	BRCW901A08	8 metre cord to connect hard wired remote controller to fan coil unit – a connection cord (3 or 8m cord is required)
Wiring adaptor [normal open contact - normal open pulse contact]	KRP413AB1S	Adaptor for remote on/off control and run & fault monitoring of unit
Wi-Fi adaptor for smartphones	BRP069A42	Adaptor for Wi-Fi interface control of unit
Interface adaptor for DIII-NET	KRP928BB2S	Adaptor for interfacing with centralised control devices. Includes remote on/off control and run & fault monitoring of unit
Intelligent Touch Controller	DCS601C51	Central controller to provide single point control of up to 64 indoor units
Photocatalytic deodorising filter with frame	KAZ917B41	Deodorising filter
Photocatalytic deodorising filter without frame	KAZ917B42	Replacement filter membrane for above
Air-purifying filter with frame	KAF925B41	Fine air purification filter
Anti-theft protection for remote control	KKF917AA4	Restraining chain to connect Infrared controller handset to holder

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



FSC

Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com