



## Large concealed ceiling unit

### High static ducted - VRV indoor unit

## FXMQ-MB

### Perfect for large area's requiring extensive ductwork runs

The large concealed ceiling unit is perfect for flexible applications for large area's requiring extensive ductwork runs.

The Daikin VRV indoor unit range is one of the widest on the market, offering no less than 26 stylish and elegant models in 116 different variants – all designed to maximise comfort, minimise operating noise and simplify installation and servicing.

Designed to fit rooms of any size and shape, Daikin indoor units are also user friendly, ultra reliable, easy to control and quiet in operation.

All indoors units comply with the Ecodesign legislation by adopting DC fans in all indoor units, improving their energy efficiency.

#### Features and benefits:

- > Up to 270Pa external static pressure allows extensive ductwork runs and flexible application: ideal for use in large areas
- > Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
- > Up to 31.5kW in heating mode



FXMQ-MB



BRC1H519W7



BRC4C65

## FXMQ-MB

Indoor Units			FXMQ200MB	FXMQ250MB
Capacity	UK Total Cooling	kW	18.0	22.5
	UK Sensible Cooling	kW	14.9	18.5
	UK Heating	kW	22.4	28.0
	Nominal Cooling	kW	25.0	31.5
	Nominal Heating	kW	0.967	1.200
Air Flow Rate	High	m³/sec	0.900	1.117
	Nom	m³/sec	0.833	1.033
	Low	m³/sec	270	270
External Static pressure	High	Pa	160	170
	Low	Pa	132.0	147.0
Dimensions	Height x Width x Depth	mm	470 x 1380 x 1100	
Weight		kg	132	132
Electrical Details	Running Current	amps	10.3	10.3
	Power Supply	Phase / Hz / V	1 / 50 / 230	
	Fuse Rating	amps	13	
Sound Level	Sound Pressure	High dBA	48.0	48.0
		Low dBA	45.0	45.0
	Sound Power	dBA	76.0	76.0
Piping Connections	Liquid	inch (mm)	3/8 (9.5)	3/8 (9.5)
	Gas	inch (mm)	3/4 (19)	7/8 (22.2)

## Options &amp; accessories

Infrared remote control including receiver (Heat Pump)	BRC4C65
"User-friendly wired remote controller with premium design (White) / (Silver) / (Black)"	BRC1H519W/S/B
Wired remote control with full-text interface and back-light	BRC1E53A/B/C
Standard wired remote control with weekly timer *4	BRC1D52
Simplified remote control (with operation mode button)	BRC2E52C
Simplified remote control (without operation mode button)	BRC3E52C
Intelligent Tablet Controller	DCC601A51
intelligent Touch Controller	DCS601C51
Intelligent Touch Manager	DCM601A51
DIII-net modbus interface	EKMBDXA
KNX interface	KLIC-DI
BACnet interface	DMS502A51
LowWorks interface	DMS504B51
Wiring adapter for external monitoring/control via dry contacts and setpoint control via 0-140Ω	KRP4A53
Wiring adapter for external central monitoring/control (controls 1 entire system)	KRP2A52
External control adapter for outdoor unit (installation on indoor unit)	DTA104A61
Adapter for multi-tenant applications (24VAC PCB power supply interface)	DTA114A61
Digital input adapter *2 *11	BRP7A51
Installation box / Mounting plate for adapter PCBs (For units where there is no space in the switchbox)	UK.FB2
External wired temperature sensor	KRCS01-4
External wireless temperature sensor	K.RSS
Wire Harness, required for connection to K.RSS	EKEWTSC
Connector for forced-off contact	Standard
Filter frame and filter	UK.FF8

(2) Installation box is necessary for these adapters

(4) Not recommended because of the limitation of the functions

(11) Only possible in combination with BRC1H\* / BRC1/2/3E\*

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



FSC

Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)